

MicroSeal™ Water Repellent



performance
solutions

COAT · PROTECT · RESTORE

freephone 0800 999 122

email info@performancesolutionsnz.co.nz

web performancesolutionsnz.co.nz

MicroSeal Don'ts

MicroSeal, as the data sheet states, is a penetrating water repellent coating. It is not a water proofing membrane so it is important to make this distinction. Read the technical data sheet for optimum application conditions and instructions.

- **Don't** apply MicroSeal over a treated surface. MicroSeal needs to be the first coating down. It is either a standalone penetrating water repellent over an untreated surface. Or a primer for a paint system or VandlGuard.
- **Don't** use MicroSeal as a water proofing membrane. It is not a membrane and **will not** cover cracks, holes or imperfections in/on the substrate. These need to be addressed prior to the application of MicroSeal.
- **Don't** apply via brush or roller application. MicroSeal is best sprayed on with a low pressure high volume sprayer (back-pack sprayer is ideal). MicroSeal has a very low viscosity, so attempting to apply it with a roller or brush would only prolong the application. Application details in the data sheet.
- **Don't** promote MicroSeal as a surface coating. It will not change the surface appearance of the substrate as MicroSeal sits below the surface (5mm). If you are looking for a "finish" then do not use MicroSeal.
- **Don't** apply in the rain.
- **Don't** apply if the moisture content inside the concrete is above 30%.
- **Do** contact me if you have any queries

PLEASE DON'T HESITATE TO CONTACT PERFORMANCE SOLUTIONS ON 0800 999 122
IF YOU HAVE ANY QUESTIONS OR REQUIRE APPLICATION ADVISE.