



VandlGuard Don'ts

VandlGuard is a clear low-sheen anti-graffiti coating. It is designed to sit as a film on top of the substrate. It will work over any paint system – as long as it is fully cured. Read the technical data sheet for optimum application conditions and instructions.

- **Don't** under-apply. VandlGuard is a 2 coat system. Coverage rate is appx 5m² per litre for each coat. It is better to over apply than under apply.
- **Don't** think that all graffiti can be easily removed. In some cases it can be, but a lot will depend on what the tagger has used and the substrate that has been attacked. An attack over a precast concrete surface can be easily addressed. An attack over uneven surfaces such as aggregate or split-faced block work will require more work. In these cases it is easier to call in specialist graffiti removers as they have the technology to remove the tag whilst leaving the VandlGuard coating in tact.
- **Don't** apply over a surface that already has an existing anti-graffiti coating over it.
- **Don't** apply VandlGuard over a bare or untreated surface. MicroSeal is a primer for VandlGuard if it is being applied in this way.
- **Don't** apply with a roller or brush. Apply with a low pressure high volume spray unit. (back-pack sprayer)
- **Do** contact me if you have any queries

PLEASE DON'T HESITATE TO CONTACT PERFORMANCE SOLUTIONS ON 0800 999 122
IF YOU HAVE ANY QUESTIONS OR REQUIRE APPLICATION ADVISE.